

STANLEY® DIE-CAST HANDLE COMBINATION SQUARE

- Embossed hard-chrome blade is coated to resist rust.
- Built-in scriber comes in handy for surface marking.
- Easy-to-read vial.
- Durable, black die-cast metal handle.



Product #	Blade Length	Type	Level	Square
46-222	12 in (305 mm)	English	1	45°, 90°

STANLEY® PLASTIC HANDLE COMBINATION SQUARE

- Embossed hard-chrome blade is coated to resist rust.
- Easy-to-read vial.
- Lightweight, plastic handle.



Product #	Blade Length	Type	Level	Square
46-012	12 in (305 mm)	English	1	45°, 90°

STANLEY® INTELLILASER™ 500 PRO STUD SENSOR AND LASER LINE LEVEL

- Detects wood/metal studs through multiple wall thicknesses (1/2", 1", 1-1/2").
- Continuous live wire detection.
- LCD screen is backlit for visibility when detecting studs.
- Versatile 2-laser set can be used separately or together to create horizontal and vertical laser cross lines.
- Projects laser lines up to 20 feet onto a work surface.
- Unique adhesive dots used to mount the laser module to most walls for hands-free operation (8 included).
- Required batteries - 9 Volt and 2 AAA (not included).



Product #	Scan Depth	Batteries (not included)	Line Level	Stud Sensor
77-500	1/2, 1, 1-1/2 in (13, 25, 38 mm)	(1) 9V & (2) AAA	7-3/4 in (197 mm) 3 (1 Level, 2 Plumb Vials)	3 in

STANLEY® FATMAX® STUD SENSOR 300



- Backlit LCD screen clearly displays all of the sensor's readings, even in low light conditions.
- Wood and metal stud detection through up to 1-1/2" deep surface material.
- AC detection identifies live wires up to 2" deep.
- OnePass™ Center-Find Technology locates stud centers.
- Deep metal scan senses metal through up to 3" of material.
- Auto calibration.
- Marking channel helps improve accuracy of marking-out readings.
- Ergonomic design and soft grip buttons provide comfort and control.



Product #	Scan Depth	Length	Width	Height	Batteries (not included)
FMHT77407	1-1/2 in (38mm)	6-1/2 in (165 mm)	3-1/2 in (90 mm)	1-1/2 in (38 mm)	(1) 9V

STANLEY® STUD SENSOR 200

- LCD screen clearly displays all of the sensor's readings.
- Wood and metal stud detection through up to 3/4" deep surface material.
- AC detection identifies live wires up to 2" deep.
- OnePass™ Center-Find Technology locates stud centers.
- Marking channel helps improve accuracy of marking-out readings.
- Ergonomic design and soft grip buttons provide comfort and control.



Product #	Scan Depth	Length	Width	Height	Batteries (not included)
STHT77406	3/4 in (19 mm)	5-5/8 in (143 mm)	3 in (76 mm)	1-3/8 in (35 mm)	(1) 9V

STANLEY® STUD SENSOR 150

- Wood and metal stud detection through up to 1-1/2" below surface material.
- AC detection identifies live wires up to 2" deep.
- Sequential LEDs and audible beeps indicates reading.
- Marking channel with LED identifies target and makes marking surfaces easy and accurate.
- Ergonomic design and soft grip buttons provide comfort and control.



Product #	Scan Depth	Length	Width	Height	Batteries (not included)
STHT77404	1-1/2 in (38 mm)	5-3/4 in (146 mm)	2-7/8 in (73 mm) in	1-3/8 in (35 mm) in	(1) 9V



STANLEY® STUD SENSOR 100

- Wood and metal stud detection through up to 3/4" deep surface material.
- AC detection identifies live wires up to 2" deep.
- Sequential LEDs and audible beeps indicates tool is reading surface.
- Marking channel with LED identifies target and makes marking surfaces easy and accurate.
- Ergonomic design and soft grip buttons provide comfort and control.



Product #	Scan Depth	Length	Width	Height	Batteries (not included)
STHT77403	3/4 in (19 mm)	5-1/8 in (130 mm)	2-1/4 in (57 mm)	1-1/2 in (38 mm)	(1) 9V

STANLEY® STUD SENSOR 50

- Detects wood/metal studs up to a 3/4" depth.
- Visual indicators on face of stud sensor for easy readability.
- LED display indicates stud edge.



Product #	Scan Depth	Length	Batteries (not included)
77-050	3/4 in (19 mm)	5-1/4 in (133 mm)	(1) 9V

STANLEY® STUD FINDER

- Provides dependable detection of wall studs.
- Magnet works by locating steel nails and screws used to hold drywall to studs.
- Base of the stud finder is notched for convenient marking once studs are located.



Product #	Length	Width	Height
47-400	1-3/8 in (35 mm)	1-3/8 in (35 mm)	1-1/4 in (31.7 mm)

STANLEY® INTELLIMEASURE® DISTANCE ESTIMATOR

- Ultrasonic distance estimator measures distances up to 40 feet.
- Large, easy-to-read LCD screen always displays last three measurements for quick reference.
- Intuitively designed toggle button features three measuring modes: length, area, and volume.
- Accurate measurements (+/-0.5%).
- Choose between English (in/ft, yds) or Metric (mm/m) modes.
- Automatically calculates area and volume.
- Manual addition mode for specialized calculations (i.e., perimeter).
- High-impact ABS housing.
- Automatic shut-off for longer battery life.



Product #	Measuring Distance	Length	Batteries (not included)
77-018	40 ft	5-1/2 in (140 mm)	(1) 9V

